

MODEL 10KD - 4WD/4WS**GENERAL SPECIFICATIONS**

LOAD CAPACITY	150,000#
LEVEL DRAWBAR PULL	10,000#
TURNING RADIUS	60"
MAXIMUM SPEED	5 MPH
WEIGHT	12,000#
LENGTH	147.25"
HEIGHT	48.5"
WIDTH	87"
CHASSIS	2 1/2" STEEL PLATE
BODY	3/8" STEEL
HITCH PINTLE	
LAMPS	4 WIDE ANGLE FOG/ TURN SIGNALS

TOOLS/STORAGE BOXES

DRIVE WHL. TIRES (4) 265/75 R - 16
TRANSMISSION DUAL HYDROSTATIC

OPERATOR'S STATION/SAFETY FEATURES

FIRE EXTINGUISHER ABC MARING
PARKING BRAKE FAIL SAFE
STEERING LEVERS (2) INDEP. WHEEL CONTROL
HOURMETER GAUGE
VOLTMETER GAUGE
ENGINE OIL PRESSURE GAUGE
ENGINE OIL TEMP. GAUGE
HYDRAULIC OIL TEMP. GAUGE

ENGINE SPECIFICATIONS

MAKE/MODEL DEUTZ BF4L 2011F
FUEL DIESEL/JET A
NO. OF CYLINDERS 4
DISPLACEMENT 167 CUBIC IN. 2.732 L
MAX SPEED 2,800 RPM
POWER RATING 75 HP
COOLING MEDIUM AIR/OIL
AIR CLEANER DRY ELEMENT
OIL FILTER SPIN ON TYPE
COLD WEATHER AID STARTING GLOW PLUG
FUEL TANK CAPACITY 25 GALLONS
FUEL CAP W/LOCKABLE LATCH
FUEL LEVEL ELECTRIC GAUGE
ELECTRIC SYSTEM 12 VOLT 60 AMP

ENGINE OPTIONS

- FORD LRG425EFI GAS/LPG ENGINE
- DUAL FUEL (GAS/LPG)
- OTHER OPTIONS CONTACT FACTORY

HYDRAULIC TRANSMISSION SPECS.

PUMPS 3.3 CU. IN./REV.
MAX. OUTPUT (EA.) 30 GPM
HYD. MOTORS (2) 3.3 CU. IN./REV.
WHL. DRIVE TYPE PLANETARY
OIL RESERVOIR CAP. 25 GALLONS
OIL LEVEL SIGHT GAUGE
OIL FILTER 10 MICRON FULL FLOW
OIL TYPE ISO 46/48

**LYNCO TUGGER CORPORATION**

a W.H. Fetzer Industries Company

401 Industrial Park Drive | P.O. Box 45 | Plymouth, Ohio 44865 USA

Phone 419.687.7309 | Fax 419.687.4651

E-mail: Sales@LyncoTugger.com www.LyncoTugger.com